


## felt handles for softwall · use guide









step 3

step 1

step 2

## set up

step 1: Lay softwall on floor or table and line up template parallel to edges of softwall and across 3rd hole from the bottom. Using a pencil, lightly trace the bottom edges of the template indicated by the black bars onto softwall. IMPORTANT: Orient template on the 3rd hole from the bottom. Bottom of softwall has rounded corners

step 2: Remove adhesive backing and align handle between pencil marks and along the inside edge of the magnetic strip.

step 3: Press felt on firmly, smoothing out the entire surface with your hand. Let sit for 24 hrs. to cure adhesive. Pulling on handles directly after application may weaken the bond and prevent them from proper attachment.

## use + care

· Ensure that the floor surface is flat, clean and dry before setting up softwall.

· textile softwall + softblock are water, tear and UV resistant (will not discolour in sunlight).

 $\cdot$  kraft paper softwall + softblock are not suitable for wet or humid environments.

· Baby wipes work well for cleaning textile softwall + softblock (or any nonabrasive cloth + water). If there is a stubborn stain on textile softwall try "Mr. Clean magic eraser", use with care as they can abrade the textile.

• textile softwall + softblock are made from an antistatic material which does not attract dust. Compressing and then expanding softwall + softblock will push air through the cells, blowing out dust that has collected inside.

· When cleaning the floors, we recommend compressing and storing your softwall on the stainless steel wall hook provided, to keep the bottom of softwalls clean and uncrumpled.

· It is possible to repair small tears in softwall, ask for details.

· softwall + softblock will benefit from periodically being closed and left in a compressed state for a few days in order to regain shape memory.

Designed by Stephanie Forsythe and Todd MacAllen, manufactured by molo and protected by one or more patents and/or design registrations held by molo, viewable at molodesign.com/ip