



## set up

**step 1:** Ensure that floor is flat, clean and dry before setting up softwall. Stand softwall with rounded edge on bottom. With a person at each end of the softwall, take a firm hold on the circular hole handles.

**step 2:** Stretch softwall. Pull until you can feel strong tension from the person on the other end, then hold it in that position for a minute. When pulling softwall open, lift ends of wall 3cm (1") off floor. If the wall is not staying open to the length you would like (max. length of 4.5m (15')), repeat the stretching process. Note: paper softwall uses a stiffer material and requires extra stretching.

**step 3:** Fold each magnetic end panel vertically onto itself as shown in diagram above. This stabilizes softwall so that it is completely freestanding. You may also connect the magnetic end panels of one softwall to that of an adjacent softwall to create longer expanses, or connect it to other steel surfaces. Please ask molo about the steel strip accessory which can provide an anchor point for softwalls.

**step 4:** To rearrange the position / shape of the softwall, hold the fins between your knuckles, lift gently and pull into place. Pulling softwall is better than pushing into desired position, as pushing may crush and soften the fins on the bottom of the wall. You can arrange softwall into any position by holding the optional felt handle, or use the handle to open and close softwall like a door.

## use + care

- textile softwall + softblock are water, tear and UV resistant (will not discolour in sunlight).
- kraft paper softwall + softblock are not suitable for wet or humid environments.
- When cleaning floors, store softwall on the stainless steel wall hook to avoid damaging / dirtying the base. For safe and easy retrieval, hang 6' and 8' softwalls by the sixth hole from the bottom. For a sculptural touch, the magnetic end panels may close around the hook to form a half column
- Baby wipes work well for cleaning textile softwall + softblock (or any nonabrasive cloth + water). If there is a stubborn stain on textile softwall try "Mr. Clean magic eraser". Use with care as they can abrade the textile.
- textile softwall + softblock are made from an antistatic material which does not attract dust. Compressing and then expanding softwall + softblock will push air through the cells, blowing out dust that has collected inside.
- softwall + softblock will benefit from periodically being closed and left in a compressed state for a few days in order to regain shape memory.
- Clean optional wool felt handles with a lint brush or damp cloth.
- It is possible to repair small tears in softwall, ask for details.
- softwall + softblock are intended to have a long, useful life. Nevertheless, they are made with material that is 100% recyclable (just remove magnetic end panels). textile softwall is 100% polyethylene and is ♻️ in the recycling stream.